

Unleash efficiency, trust reliability!

Spinn 2.2–7.5 Variable Speed / Fixed Speed



# Introducing Spinn 2.2–7.5

Improved productivity, reduced energy consumption, and a lasting reputation for steadfast reliability.

The ABAC Spinn screw compressor is an excellent choice for those seeking comfort and efficiency at work.

This compact compressor boasts significantly lower noise levels, making it easy to install close to the point of use.

With its high-performance levels and simple maintenance, the Spinn is versatile and can be installed in various environments such as metalworking, woodworking, stoneworking, and sandblasting. Its efficiency and reliability ensure that all applications are handled with ease.





# Revolutionising savings and sustainability for a brighter future.

The ABAC Spinn 2.2-7.5 VSD compressors are the ultimate solution for reliable and long-lasting performance.

Thanks to their innovative technology, they are more dependable than ever before.

With Variable Speed Drive, these compressors can operate at lower speeds, which means less wear and tear on their components.


Your compressor no longer runs at 100% capacity when not needed.

Unlike compressors continuously running at maximum speed, VSD compressors experience lower peak currents and load surges, thanks to soft and controlled starts/stops.

This helps to reduce the stress on the mechanical and power electronics, ultimately extending the compressor's lifespan compared to fixed-speed models.

With the ABAC Spinn 2.2-7.5 VSD compressors, experience the highest levels of efficiency and reliability!







# Spinn 2.2–7.5 Variable Speed

# Revolutionising savings and sustainability for a better tomorrow.

**Upgrade your compressor game with Spinn 2.2-7.5 Variable Speed Drive!** 

Save up to 30% on energy costs while enjoying the latest and greatest technology for a new generation.

### Reliability

Rev up your motors with ease! Our soft starter delivers controlled and gradual acceleration for your motor, with up to 80% less force on main components during start-up than at fixed speed. Say goodbye to mechanical stress on your motor and bearings and hello to smooth sailing!

### Savings

Save up to 30% on energy with our latest Spinn model compared to fixed speed models! With advanced features that boost efficiency, you can enjoy maximum savings while still getting the needed performance.

### Small & Silent

Our compressor is designed for quiet operation at just 57 dB(A). Its compact footprint and our all-in one solution provide ample air storage and flexible installation options, making it perfect for use on your production floor without causing distractions.

#### // Robust

Designed with a plug-and-play installation solution and suitable for intermittent operation, it can withstand ambient temperatures up to 46°C with a wide range of options.







# Introducing the all-in-one VSD compressor, with a range of features designed to make your life easier.

### Main features

The force driving the product

### Next generation air end technology

 Our advanced screw air end ensures uninterrupted operation, eliminating the need for cool-down intervals. Engineered in-house for greater air delivery efficiency



#### **IE3 Motor**

- Efficient power consumption
- Proven component with outstanding dependability

### New INFOLOGIC<sub>2</sub> connect controller

- Simple setup, monitoring, and control
- Uptime increased thanks to the successful integration of notification and shutdown alarm systems



#### **Inverter**

- · Modulation of speed
- Reduce stress on main components
- Reliable and well-known supplier



#### **Benefits of installing on-site**

Thanks to its quiet operation and integrated design, the Spinn VSD can be installed near the point of use without requiring a separate compressor room, saving on floor space, piping, and installation costs.



# Introducing the INFOLOGIC<sub>2</sub> connect controller - the ultimate solution for hassle-free compressor operation!

The state-of-the-art Infologic2 connect controller provides the following benefits to optimise the performance of your compressor:

- · Large, intuitive display
- Delayed Second Stop energy savings
- Real-time warnings and shutdown alarms
- Service status, history and notifications
- Easily adjust pressure band settings



# Spinn 2.2–7.5 Fixed Speed

Looking for a reliable Oil Injected Screw compressor that can handle continuous duty cycle applications?

## Look no further than Spinn 2.2-7.5 Fixed Speed!

With significantly improved performance compared to other market brands, this renowned and reliable solution is the perfect partner for all your needs.

The ABAC Spinn range offers outstanding cost savings on installation and piping, all in a sleek and efficient design.





# Work consistently and without interruption

You don't have to wait for the compressor to cool down with the Spinn, so you can keep things moving and boost productivity all day long!



## A higher level of air quality

When you use a Spinn compressor, you not only get cleaner air quality, but you also protect your pneumatic tools. It has an oil carry-over of less than five parts per million, typically six times less than a piston compressor. As a result, maintenance on downstream equipment is significantly reduced or even eliminated.



# Reduced power consumption

The Spinn's innovative compression technology allows it to produce air more efficiently than traditional piston compressors, giving you maximum performance with minimum energy consumption.



# A quieter workplace

The Spinn 2.2-7.5 is impressively quiet, producing only 61 to 68 dB(A) - more silent than the average piston compressor by 20 dB(A)!



### Basic controller

Operating the compressor is a breeze, with all the necessary information at your fingertips. And that's not all - enjoy added perks like monitoring running and loading hours, remote start/ stop, automatic restart, and failure warnings, giving you the ultimate flexibility and control.





### **Highly efficient**

IE3 motors 100% duty cycle and IP55 protection



#### **Highly dependable**

The air end is designed to provide exceptional performance and efficient energy usage.

### **Spinn 2.2-7.5**

### **Fixed Speed**

- Industry-leading Free Air Delivery
- Continuous duty
- Advanced controller
- Floor-mounted and tankmounted models
- Optional condensation prevention package
- Optional clean air version with integrated dryer and filters
- Super silent

### **Spinn 2.2-7.5**

### **VSD**

- Industry-leading Free Air Delivery
- Continuous duty
- Advanced controller
- Floor-mounted and tankmounted models
- Optional condensation prevention package
- Optional clean air version with integrated dryer and filters
- Up to 7 decibels quieter than fixed-speed
- Energy savings of up to 30% compared to fixed-speed
- Less component wear for a longer lifetime and lower operational costs
- Lower starting currents increase reliability

### **Options**

#### Improve and personalise your Spinn.

With its wide range of options and flexible build, the Spinn 2.2-7.5 can meet all of your needs.



Line filter

Can be added for high-quality air.



No-loss timer drain

Removes tank condensation.



500-litre tank

Get more air storage and say goodbye to condensation worries.



C Oil heater

Ensures no intermittent-use condensation by keeping the oil temperature constant during unloading or idle periods.



**Tropical thermostat** 

Maintain a higher oil temperature, reducing the risk of condensation.

### **Technical specifications**

### **Fixed speed**

| Model        | Max.<br>working<br>pressure | Reference<br>working<br>pressure | Free Air Delivery<br>@ reference conditions* |       |      | Motor<br>power |     | Noise<br>level ** |
|--------------|-----------------------------|----------------------------------|--|-------|------|----------------|-----|-------------------|
|              | Bar                         | Bar                              | m3/h   | I/min | cfm  | kW             | hp  | db(A)             |
| SPINN        | 8                           | 7.5                              | 20.6   | 343   | 12.1 | 0.0            | 0   | 04                |
| 2.2          | 10                          | 9.5                              | 16.9   | 281   | 9.9  | 2.2            | 3   | 61                |
| SPINN<br>3   | 8                           | 7.5                              | 27.6   | 460   | 16.2 | 3              | 4   | 61                |
|              | 10                          | 9.5                              | 21.5   | 359   | 12.7 |                |     |                   |
| SPINN        | 8                           | 7.5                              | 34.7   | 578   | 20.4 | 3              | 4   | 61                |
| 4            | 10                          | 9.5                              | 30.1   | 502   | 17.7 |                |     | 61                |
| SPINN<br>5.5 | 8                           | 7.5                              | 51.5   | 858   | 30.3 | 5.5            | 7.5 | 66                |
|              | 10                          | 9.5                              | 45.4   | 756   | 26.7 |                |     |                   |
| SPINN<br>7.5 | 8                           | 7.5                              | 61.7   | 1028  | 36.3 | 7.5            | 10  | 68                |
|              | 10                          | 9.5                              | 57.7   | 961   | 33.9 | 7.5            |     |                   |

| Weight           |                            |                                    |                            |                                    |
|------------------|----------------------------|------------------------------------|----------------------------|------------------------------------|
| Base-<br>mounted | Tank-<br>mounted<br>200 L. | Tank-<br>mounted<br>200 L. + dryer | Tank-<br>mounted<br>270 L. | Tank-<br>mounted<br>270 L. + dryer |
| kg               |                            |                                    |                            |                                    |
| 110              | 165                        | 190                                | 180                        | 205                                |
| 115              | 170                        | 195                                | 185                        | 210                                |
| 120              | 175                        | 200                                | 190                        | 215                                |
| 130              | 185                        | 210                                | 200                        | 225                                |
| 140              | 195                        | 225                                | 210                        | 240                                |

### Variable speed

| Model        | Max.<br>working<br>pressure | Reference<br>working<br>pressure | Free Air Delivery<br>@ reference conditions* |       |      | Motor<br>power |     | Noise level<br>measured at<br>70% load** |
|--------------|-----------------------------|----------------------------------|--|-------|------|----------------|-----|--|
|              | Bar                         | Bar                              | m3/h   | I/min | cfm  | kW             | hp  | db(A)                                    |
| SPINN        | 8                           | 7.5                              | 21.6   | 360   | 12.7 |                | 2   | 57                                       |
| 2.2          | 10                          | 9.5                              | 17.6   | 293   | 10.3 | 2.2            | 3   |  |
| SPINN<br>3   | 8                           | 7.5                              | 27.6   | 460   | 16.2 | 3              | 4   | 57                                       |
|              | 10                          | 9.5                              | 21.7   | 361   | 12.7 |                |     |  |
| SPINN        | 8                           | 7.5                              | 34.9   | 581   | 20.5 | 4              | 5.5 | 58                                       |
| 4            | 10                          | 9.5                              | 30.2   | 503   | 17.8 |                |     |  |
| SPINN        | 8                           | 7.5                              | 53.6   | 894   | 31.6 | 5.5            | 7.5 | 61                                       |
| 5.5          | 10                          | 9.5                              | 45.5   | 758   | 26.8 |                | 7.5 |  |
| SPINN<br>7.5 | 8                           | 7.5                              | 62.1   | 1035  | 36.6 | 7.5            | 10  | 61                                       |
|              | 10                          | 9.5                              | 57.9   | 965   | 34.1 | 7.5            | 10  | 61                                       |

| Weight           |                           |                                   |
|------------------|---------------------------|-----------------------------------|
| Base-<br>mounted | Tank-<br>mounted<br>200L. | Tank-<br>mounted<br>200L. + dryer |
| kg               | ,                         |                                   |
| 110              | 165                       | 190                               |
| 115              | 170                       | 195                               |
| 120              | 175                       | 200                               |
| 130              | 185                       | 210                               |
| 140              | 195                       | 225                               |

<sup>\*</sup> Unit performance measured according to ISO1217, Annex C, latest edition \*\* Noise level measured according to ISO2151 2004.



### **Dimensions**

**Base-mounted** 

Tank-mounted 200 L.

Tank-mounted 270 L.

Tank-mounted 500 L.

Tank-mounted 200 L. + dryer

Tank-mounted 270 L. + dryer

Tank-mounted 500 L. + dryer

| _ |     |          |    |         |                       |
|---|-----|----------|----|---------|-----------------------|
| - | ixe | <b>~</b> | en |         | $\boldsymbol{\alpha}$ |
|   |     | u        | JΡ | <u></u> | u                     |

| Length | Width | Height |
|--------|-------|--------|
| mm     |       |        |
| 620    | 630   | 950    |
| 1430   | 600   | 1260   |
| 1540   | 600   | 1350   |
| 1940   | 605   | 1500   |

### Variable speed

| Length<br>mm | Width | Height |
|--------------|-------|--------|
| 620          | 630   | 955    |
| 1430         | 600   | 1265   |
| N/A          | N/A   | N/A    |
| 1540         | 600   | 1350   |
| N/A          | N/A   | N/A    |

<sup>\* 270</sup>L with Dryer available for variable speed with AD2000







ç

Unleash efficiency, trust reliability! Spinn 2.2–7.5 Variable Speed / Fixed Speed ©ABAC 2024

The contents of this publication are the copyright of the publisher and may not be reproduced (even extracts) unless prior written permission is granted. Every care has been taken to ensure the accuracy of the information contained in this publication but no liability can be accepted for any loss or damage whether direct, indirect or consequential arising out of the use of the information contained herein.